

ALFA LIGHT



technology on your side



Alfa Light exposure unit comes in 4 sizes: 70 x 100 cm, 100 x 125 cm, 125 x 125 cm and 125 x 160 cm. Standard configuration with vacuum on top gives simplicity of use. Brand name elements used, assure long life for machine.

Great advantage is shutter exposure system. In stand by mode shutter is locked, while exposure its open. It longer lifetime of UV lamp and makes rapid start exposure procedure.

Touch screen control, UV light integrator for precise amount of UV units. Automatic cycle mode and manual exposure for operator's convenience.

Compact design, strong welded construction assure convenience of use.

STANDARD FEATURES

Construction

- rigid welded construction
- laser cutted for precision
- powder coated

Accessibility

- easily accessible side walls for service

Exposure

- metall halide 2 kW UV lamp
- UV lamp mechanical shutter
- STAND BY mode
- UV light integrator

Software

- Software is constantly proved also according to printers suggestions

Safety

- control panel is gently hidden from mistaken use
- safety micro switch securing from UV operator's exposition

Cost efficiency

- long UV lamp live due to reduced start/stop cycles
- stand by mode (option), for power down while STAND BY

Warranty and service

- 2 year warranty
- service agreement on special conditions

options

- STAND BY mode

	ALFA LIGHT 70x100	ALFA LIGHT 100x125	ALFA LIGHT 125x125	ALFA LIGHT 160x125
Size of frame cm	70 x 100 cm	100 x 125 cm	125 x 125 cm	160 x 125
Electrical requirements	400V, 3PH, 2.5 kW, 32A CEE-plug			
Dimensions L x W x H cm	132 x 95 x 120 cm	127 x 151 x 120 cm	152 x 151 x 120 cm	187 x 151 x 120 cm
Standarised Exposition time	26 sec	28 sec	30 sec	33 sec
Shipping weight	190 kg	260 kg	320 kg	390 kg

