

ELECTRIC DRYER DEL-2479A

60 cm belt width, heat chamber 200cm

Machine

1	Total length	300 cm		
2	Heat chamber length	200 cm		
3	Belt width	60 cm		
4	Inlet / outlet length	50 cm		
5	High	115 cm		
6	Electrical requirements	400V, 3PH, 8.8 kW, 32A CEE-plug		
7	Belt rotation direction	Both side (left & right)		
8	Belt drive	frequency converter, sleeplessly adjustable		
9	Belt type	fiberglass Teflon coated, 4x4 mm mesh-size		
10	Exhaust connection	100 mm		
11	Heating elements	3.3 um IR wave length		
12	Temperature control	PID		
13	Cool skin technology	150 mm insulation 4 walls		
14	If equipped with Hot air circulation cures wide range of inks with all substrates (also paper and plastic)	Plastisol Inks	Water base Inks	Solvent Inks
15	Guarantee	2 years limited warranty		
16	Production capacity (curing element size 40 x 50 cm, curing conditions 1 min in 160°C)	300 pcs/hr		

MACHINE EQUIPMENT IN OPTION

17	Wheels option per 1 oven	YES	1		
18	Hot air circulation* per 1 oven (1300 m ³ /h)	YES	1		
19	Cooling System	NO	0		